Required Infor	Note: For vertical turb	ines please refer to the Vertical Turn	bine Quote Form.	
Mechanical seal being used:		Flush availabl	e: No Yes Flush Rate:	
Units of measureme	nt: 🗌 Inch 📄 Metric	Shaft rotation	as viewed from the motor end: s require both R and L devices)	
Shaft size: (or rotating element: sleeve, impeller hub, seal OD etc.)				
	First obstruction:			
Version F (Flush required)	□ N (Non fibrous application	s) 🔲 D (Fibrous applicat	tions) C (Chemical intermittent applications)	
Installation Type A a width: Ø b diameter: *option depends on throat diameter		drilled air vent option*	Type B + + + + + + + + + +	
Type E a width: Øb diameter: c width: Ød diameter: Øe diameter:		Type I	□ Type S	
Material ESC (Carbon fill 316 Stainless St 416 Stainless St	ed PTFE) eel RPM:	formation	Distributor Company: Specialist: P.O.#: Customer:	
17-4PH Stainles BRZ (660 Bronz Other:	e) Temperatur	re:		

This document is available online at *enviroseal.ca*. EnviroSeal Terms & Conditions of Sale is available online at *enviroseal.ca/terms_of_sale*. The purchaser is responsible for ensuring the dimensions, quantity and applications suitability meet end user requirements. Please email filled out form to *support@enviroseal.ca*.

Patent Protected Worldwide. SpiralTrac is a trademark of EnviroSeal Engineering Products Ltd.